

PVC Coated Blockout Double-Sided Banner 550 FR B1

High opacity and smoothness for excellent double sided printing, most suited to indoor use.

FEATURES AND BENEFITS

- Fire rated to B1 certification
- Suitable for indoor and outdoor use
- Premium grade product
- Available in 3.2m and 5.0m widths
- Double sided printing

Suitable for use with:



Order Code	W (mm)	L (mm)	Weight (gm sq)
ISB274159	950	30	550
ISB274339	1100	30	550
ISB273763	1370	30	550
ISB273766	1600	30	550
ISB274351	1600	50	550
ISB274537	2030	30	550
ISB273772	2500	50	550
ISB274291	3200	50	550
ISB274513	5000	50	550

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.

PVC Coated Blockout Double-Sided Banner 550 FR B1

TECHNICAL SPECIFICATIONS

Properties	Test Method	Result	Unit
Total Weight	DIN53352 BS3424	550	g/sq.m
Tensile Strength (W/F)	DIN 53354 BS3424	1290/1020	N/5cm
Tear Resistance (W/F)	DIN 53356 BS3424	110/100	N/5cm
Welding Adhesion	DIN 53357 BS3425	80	N/5cm
Temperature Resistance	DIN 53372 BS3424	-20 - +70	°C
Max Width		5.0	Meter
Flame Retardant	NFPA-701, DIN4102-B1	B1	

NOTE: Information listed above is based on our general experience and observation and is given in good faith and does not constitute terms or part of any contract. We will not accept responsibilities with respects to factors outside our knowledge, including direct, indirect or consequential loss. Values without tolerance statements are values with a tolerance of $\pm 5\%$. Media will often have a natural base, therefore there can be variances from batch to batch. Shelf life is 2 years, storage temperature 15-25 °C, RH 40-60%. Repack opened rolls when not in use. Allow material to adapt to room conditions for 24 hours prior to printing. We always recommend a test print and the customer is deemed to have ensured suitability of the material for the application intended and assumes all associated risks and liabilities in connection with specifying, using or not being able to use any product. Always hem edges when used in hanging or suspended applications by high-tack banner tape or welding. Grommets or eyelets should always be inserted in double-hemmed edges, four layers at corners. Remember that sewing in some applications can affect the integrity of the media. Technical specifications may change without notice. E & OE.