



Issue date : 05/01/2005

Date last modification: 09/12/2016

RI-JET 100 GLOSS WHITE AP PERMANENT

Face Material

Gloss white monomeric vinyl film.

Type Monomeric vinyl Colour and Finish Gloss white

Weight 134 g/m 2 ±10% ISO-536 Thickness 100 μ ±10% ISO 534-80

Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference AP permanent
Type Acrylic permanent
Min. Appl. Temp. +10°C

Min. Appl. Temp. +10°C
Service Temp. -30°C/

Service Temp. -30°C/+120°C Shear Medium

Tack Medium N/inch² Final Adhesion High N/inch

Liner

Type One side siliconised clay coated

Kraft

Colour and Finish White

Weight 135 g/m² PP-032 - ISO

±10% 536

Thickness 145 μ ±10% ISO 534 Transparency n.a. % DIN 53 147-64

Applications

For advertising and promotional applications (window graphics and outdoor and indoor posters, billboards and signs) and for vehicle applications (flat sided including buses, trams and taxis).

Printing Methods

The RI-JET series of ink-jet print media gives excellent print results with UV, solvent and eco-solvent ink-jet printing. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of $22^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and 50 \pm 5% of Relative Humidity.
- · Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.